

Series			airHome 600					
Model		Indoor Unit		RAK-VJ18PHAE	RAK-VJ25PHAE	RAK-VJ35PHAE	RAK-VJ42PHAE	RAK-VJ50PHAE
		Outdoor Unit		RAC-VJ18PHAE	RAC-VJ25PHAE	RAC-VJ35PHAE	RAC-VJ42PHAE	RAC-VJ50PHAE
CAPACITY & RATING	Nominal Capacity (Min. - Max.)	Cooling	kW	2.00 (0.90 - 2.50)	2.50 (0.90 - 3.10)	3.50 (0.90- 4.00)	4.20 (1.70- 5.00)	5.00 (1.90- 5.20)
		Heating	kW	2.50 (0.90 - 3.20)	3.40 (0.90- 4.40)	4.20 (0.90- 5.00)	5.40 (1.7- 6.00)	6.00 (2.2- 7.30)
	Energy Efficiency	SEER	8.5	8.5	8.5	7.5	7.35	
		SCOP	4.9	4.9	4.9	4.6	4.6	
	Energy Rating (Energy class)	Cooling	A+++	A+++	A+++	A++	A++	
		Heating	A++	A++	A++	A++	A++	
FEATURES	Inverter	For energy efficiency		●	●	●	●	●
	Heating function	For winter heating		●	●	●	●	●
	airCloud Home	App for remote control & scheduling		●	●	●	●	●
	FrostWash	Maintains airflow performance		●	●	●	●	●
	Mold Guard	Prevents build-up of mold		●	●	●	●	●
	Smart Eco	Automated power saving		●	●	●	●	●
Air Purification Technologies	Stainless Pre-Filter	Filters large particles		●	●	●	●	●
	Air Purification Filter	ViroSense Z1 filter		●	●	●	●	●
	FrostWash	automatic self-cleaning		●	●	●	●	●
	Ionizer	Aqtiv-Ion		●	●	●	●	●
TECHNICAL SPECS	Power Supply		V / Phase / Hz	220-240V / 1Ph / 50Hz	220-240V / 1Ph / 50Hz	220-240V / 1Ph / 50Hz	220-240V / 1Ph / 50Hz	220-240V / 1Ph / 50Hz
	Nominal Cooling Power Input (Min. - Max.)		Watts	419 (250 - 1010)	549 (250 - 1290)	875 (250 - 1460)	1120 (300 - 1700)	1471 (300 - 2100)
	Nominal Heating Power Input (Min. - Max.)		Watts	519 (250 - 970)	733 (250 - 1500)	1000 (250 - 1700)	1317 (500 - 2100)	1558 (500 - 2750)
	Starting Current (cooling/heating)		Amps	2.46/2.93	3.08/3.87	4.43/5.11	5.10/5.99	6.69/7.09
	Running Current (cooling/heating)		Amps	1.09-4.39 /1.09-4.22	1.09-5.61 /1.09-6.52	1.09-6.35 /1.09-7.39	1.30-7.39 /2.17-8.70	1.30-8.70 /2.17-11.96
	Operation Range	Cooling	°C	-10°C~ 46°C	-10°C~ 46°C	-10°C~ 46°C	-10°C~ 46°C	-10°C~ 46°C
		Heating	°C	-15°C~21°C	-15°C~21°C	-15°C~21°C	-15°C~21°C	-15°C~21°C
	Refrigerant	Type		R32	R32	R32	R32	R32
		Current Amount	kg	0.87	0.87	0.87	1.05	1.05
	Compressor Type			ROTARY	ROTARY	ROTARY	2 Cylinder Rotary	2 Cylinder Rotary
	Diameter of Pipes	Liquid	Inch	1/4"	1/4"	1/4"	1/4"	1/4"
		Gas	Inch	3/8"	3/8"	3/8"	1/2"	1/2"
	Maximum Pipe Length		m	20	20	20	20	20
	Maximum Piping Elevation		m	10	10	10	10	10
	Dehumidification		l / h	1.2	1.4	1.6	1.8	2.0
	Indoor Unit	Dimension (W×H×D)	mm	780×280×227	780×280×227	780×280×227	780×280×227	780×280×227
		Weight	kg	8.6	8.6	8.6	8.8	8.8
		Air Flow (Max.)	m³ / h	500	550	680	720	750
		Sound Power	dB(A)	51	54	57	60	60
		Sound Pressure	dB(A)	19/22/33/36/38	20/23/34/39/41	26/27/36/42/44	27/31/39/44/46	27/31/39/44/46
	Outdoor Unit	Dimension (W×H×D)	mm	750×548×288	750×548×288	750×548×288	792×600×299	792×600×299
		Weight	kg	31.6	31.6	31.6	39.5	39.5
		Sound Power	dB(A)	58	60	61	63	63
		Sound Pressure	dB(A)	45	47	49	50	50